

# 7310

## DIGITAL VISCOMETER

TOUCH SCREEN



### TECHNICAL SPECIFICATIONS

Measuring Range(mPa.s)	20-2,000,000(mPa.s)
RPM	0.3, 0.6, 1.5, 3, 6, 12, 30, 60
No of Standard Spindles	#1,#2,#3,#4 is standard configuration,
Measurement Accuracy :	± 1.0% of range
Repeatability	±0.5%
Display	LCD Touch Screen
<b>Temperature RTD Monitoring</b>	
Sensor Probe :	Yes
Output	RS 232 Interface
Power Supply	AC 220V/50Hz
Dimension LxWxH (mm)	400 x 350 x360
Weight	9 Kg

### SALIENT FEATURES

- ✓ Stepping Motor means Accurate, reliable operation
- ✓ Direct readout of all measurement parameters
- ✓ Auto Range Showing
- ✓ Time Function for measurement
- ✓ Sound alarm at under 20% Torque
- ✓ Linear calibration
- ✓ Wide range power supply:100V-240V

### STANDARD ACCESSORIES

Ascending and falling rack	1 set
Protective frame of rotor	1 No.
Rotors	(No.1,2,3,4 each)
Power adapter	1 No.
Spanner	1 No.
Screw driver	1 No.
Socket	1 set



# 730

## DIGITAL VISCOMETER

### TECHNICAL SPECIFICATIONS

Display	LCD
Measurement Range	20-400,000 mPAS/C.P
Spindle numbers	4 Spindles
Rotor Speed (rpm)	6/ 12/30/60
Accuracy	± 5% Newtonian Fluid
Overall Dimensions	340mm x 420m m x 470mm
Net Weight	9kg



### STANDARD ACCESSORIES

Ascending and falling rack	1 set
Protective frame of rotor	1 No.
Power adapter	1 No.
Rotors	1,2,3,4 each
Spanner	1 No.
Screw driver	1 No.
Socket	1 set

